

US006819630B1

(12) United States Patent

Blackmon et al.

(10) Patent No.: US 6,819,630 B1

(45) **Date of Patent:** Nov. 16, 2004

(54) ITERATIVE DECISION FEEDBACK ADAPTIVE EQUALIZER

(75) Inventors: Fletcher A. Blackmon, Forestdale, MA (US); Mohanadreza M. Hagh,
Belmont, MA (US); John Proakis,
Andover, MA (US); Masoud Salehi,
Westwood, MA (US)

(73) Assignee: The United States of America as represented by the Secretary of the Navy, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: 10/666,829

(22) Filed: Sep. 18, 2003

Related U.S. Application Data

(60) Provisional application No. 60/412,432, filed on Sep. 20, 2002.

(51) Int. Cl.⁷ H04B 11/00

(56) References Cited

U.S. PATENT DOCUMENTS

5,301,167 A	*	4/1994	Proakis et al	367/134
5,559,757 A	*	9/1996	Catipovic et al	367/134
5,844,951 A	*	12/1998	Proakis et al	375/233
6,295,312 B	1 *	9/2001	Jarvis	367/134

* cited by examiner

Primary Examiner—Ian J. Lobo

(74) Attorney, Agent, or Firm—James M. Kasischke; Michael F. Oglo; Jean-Paul A. Nasser

(57) ABSTRACT

The present invention provides a receiver for underwater acoustic telemetry which combines a decision feedback adaptive equalizer structure with a modified turbo-equalizer structure. The modified turbo-equalizer structure is of significantly reduced complexity because the decision feedback adaptive equalizer structure is operable to process a plurality of data channels to provide a single symbol data output stream for application to the input of the modified turbo-equalizer which uses a decision feedback equalized, interleaver, deinterleaver and a decoder. Either a hard viterbidecorder for single iteration processing or a soft in/soft out decorder such as a MAP decoder for multiple iteration can be used. The iteration provide improved performance compared to a normal DFE and lower complexity compared to the traditional turbo-equalizer.

20 Claims, 4 Drawing Sheets

